






Water soluble resin composition

Patent number: CN1314931
Publication date: 2001-09-26
Inventor: TAKASHI KANDA (CH); HATSUYUKI TANAKA (CH)
Applicant: CLARIANT INTERNATIONAL LTD (CH)
Classification:
- **international:** (IPC1-7): C08L101/14; C08K5/05; C08K5/06; G03F70/04; H01L21/027
- **european:**
Application number: CN20000801157 20000616
Priority number(s): JP19990182778 19990629

Also published as:

 EP1152036 (A1)
 WO0100735 (A1)
 US6555607 (B1)
 JP2001019860 (A)
 CN1134510C (C)

Report a data error here

Abstract not available for CN1314931
Abstract of correspondent: **EP1152036**

A water-soluble resin composition comprising (1) a water-soluble resin, (2) a water-soluble crosslinking agent, (3) at least one of surface active agents selected from acetylene alcohols, acetylene glycols, polyethoxylates of acetylene alcohols and polyethoxylates of acetylene glycols, and (4) a solvent consisting of water or a mixture of water and a water-soluble solvent. This water-soluble resin composition is applied onto a resist pattern, then heated to crosslink by an acid supplied from the resist, followed by development to remove the non-crosslinked water-soluble resin coating layer. This water-soluble resin composition is excellent in coating characteristics on steps of resist patterns and in dimensional regulation upon fining of patterns so that resist patterns such as trench patterns and hole patterns can effectively be fined.

Data supplied from the **esp@cenet** database - Worldwide